NSN 5930-01-112-6048

Hazardous Locations/environmental Protection:

Push Switch - Page 1 of 2

Body Style:Panel mounted

Explosion proof

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-01-112-6048

2.755 inches
Overall Height:
0.688 inches
Overall Width:
0.688 inches
Body Width:
0.688 inches
Body Height:
0.688 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.099 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
White single actuator and white single actuator
Actuator Inscription:
On/alarm single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Central satellite communications control an/msq-114
Mounting Surface To Terminal End Distance:
2.680 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-112-6048

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0