

View Online at <https://aerobasegroup.com/nsn/5930-01-112-8498>

Body Style:

Hole mounted

Overall Length:

1.406 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Overall Width:

0.415 inches

Body Length:

1.034 inches

Body Width:

0.415 inches

Body Height:

0.625 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.110 inches

Actuator Style:

Rectangular

Actuator Width:

0.165 inches

Actuator Free Position Height:

0.578 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

1520-01-035-0266

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Actuating Force:

75.0 grams

Actuator Movement:

Between 0.010 pretravel inches and 0.050 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 6.000 amperes inductive dc and 6.000 amperes motor dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 3.000 amperes motor ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab w/screw

Specification Data:

81349-mil-s-8805/90 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0