

View Online at <https://aerobasegroup.com/nsn/5930-01-112-8499>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

1.320 inches

Overall Height:

0.672 inches

Overall Width:

0.780 inches

Bushing Length:

0.310 inches

Body Length:

0.770 inches

Body Width:

0.780 inches

Body Height:

0.672 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.323 inches

Actuator Height:

0.240 inches

Actuator Free Position Height:

0.550 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

An/sps 49956

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

24.0 ounces

Actuator Movement:

Between 0.125 pretravel inches and 0.047 overtravel inches and 0.188 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Special Features:

Flexible insulators

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0