

View Online at <https://aerobasegroup.com/nsn/5930-01-112-9617>

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

1.880 inches

Overall Height:

2.385 inches

Overall Width:

0.750 inches

Body Length:

1.380 inches

Body Width:

0.750 inches

Body Height:

0.910 inches

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.475 inches

Actuator Roller Diameter:

0.480 inches

Actuator Roller Width:

0.107 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

Truck hand li

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing and unthreaded hole

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Switch Release Force:

24.0 ounces

Switch Actuating Force:

72.0 ounces

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0