

View Online at <https://aerobasegroup.com/nsn/5930-01-112-9618>

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

1.880 inches

**Overall Height:**

2.035 inches

**Overall Width:**

0.750 inches

**Bushing Length:**

0.800 inches

**Body Length:**

1.380 inches

**Body Width:**

0.750 inches

**Body Height:**

0.910 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.325 inches

**Actuator Free Position Height:**

1.125 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**End Application:**

Truck hand li

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

**Switch Release Force:**

28.8 ounces

**Switch Actuating Force:**

64.0 ounces

**Actuator Movement:**

0.070 pretravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0