NSN 5930-01-113-1623

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-113-1623

Body Style:						
Hole mounted						
Hazardous Locations/environmental Protection:						
Watertight						
Overall Length:						
3.740 inches						
Overall Height:						
2.720 inches						
Overall Width:						
1.660 inches						
Case Material:						
Metal						
Actuator Style:						
Roller arm						
Actuator Height:						
0.940 inches						
Actuator Roller Diameter:						
0.750 inches						
Housing Height:						
1.780 inches						
Housing Length:						
2.840 inches						
Housing Width:						
1.660 inches						
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:						
2.340 inches						
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:						
1.160 inches						
Maximum Voltage Rating In Volts:						
440.0 ac and 355.0 dc						
Inclosure Type:						
Fully enclosed						
Nonpile-up Contact Arrangement:						
1 pole, double throw, one position momentary single switch unit						
Switch Actuating Force:						
32.0 ounces						
Actuator Movement:						
50.0 pretravel degrees and 10.0 overtravel degrees and 4.0 differential degrees						
Contact Load Current Rating At Maximum Rated Voltage:						
100.000 milliamperes resistive dc and 6.000 amperes resistive ac						

3 screw

Terminal Type And Quantity:

NSN 5930-01-113-1623

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0