

View Online at <https://aerobasegroup.com/nsn/5930-01-113-1754>

**Inside Diameter:**

0.125 inches single connection

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.231 inches

**Overall Height:**

2.440 inches

**Overall Width:**

2.190 inches

**Unthreaded Mounting Hole Diameter:**

0.201 inches

**Distance Between Mounting Facility Centers:**

1.250 inches

**End Application:**

F15 simulator 25500

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

90.00 pounds per square inch

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Quick disconnect, female

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

3.20 actuation point inches of water and 1.80 deactuation point inches of water and 1.40 differential point inches of water

**Contact Voltage Rating In Volts:**

250.0 ac at sea level single voltage

**Pressure Connector Type:**

Barbed, unthreaded external single connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0