

View Online at <https://aerobasegroup.com/nsn/5930-01-113-1754>

Inside Diameter:

0.125 inches single connection

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.231 inches

Overall Height:

2.440 inches

Overall Width:

2.190 inches

Unthreaded Mounting Hole Diameter:

0.201 inches

Distance Between Mounting Facility Centers:

1.250 inches

End Application:

F15 simulator 25500

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

90.00 pounds per square inch

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Quick disconnect, female

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

3.20 actuation point inches of water and 1.80 deactuation point inches of water and 1.40 differential point inches of water

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Pressure Connector Type:

Barbed, unthreaded external single connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0