

View Online at <https://aerobasegroup.com/nsn/5930-01-113-2319>

Thread Class:

3a single pressure connection

Thread Length:

0.550 inches single pressure connection

Hazardous Locations/environmental Protection:

Waterproof and corrosion resistant and fungus resistant

Overall Length:

2.500 inches

Outside Diameter:

0.438 inches single connection

Body Length:

1.325 inches

Overall Diameter:

0.750 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.750 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 300.0 degrees fahrenheit

Mounting Method:

Line

Contact Action Stimulus:

Increase

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

33.00 actuation point pounds per square inch gage and 40.00 actuation point pounds per square inch gage and 3.00 deactuation point pounds per square inch gage and 40.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0