

View Online at <https://aerobasegroup.com/nsn/5930-01-113-2989>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.780 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Height:

0.542 inches

Overall Width:

0.250 inches

Body Length:

0.780 inches

Body Width:

0.250 inches

Body Height:

0.360 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Length:

0.090 inches

Actuator Style:

Rectangular

Actuator Height:

0.037 inches

Actuator Width:

0.090 inches

Actuator Free Position Height:

0.330 inches

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

Model 4080 34984

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Actuating Force:

65.0 grams

Actuator Movement:

Between 0.025 pretravel inches and 0.035 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac

Precious Material And Location:

Contacts and terminal surfaces silver

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0