## NSN 5930-01-113-5714

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-113-5714

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
4.660 inches
Overall Height:
1.780 inches
Overall Width:
1.660 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.820 inches
Actuator Roller Diameter:
0.440 inches
Housing Height:
1.780 inches
Housing Length:
2.840 inches
Housing Width:
1.660 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.340 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.160 inches
Maximum Voltage Rating In Volts:
440.0 ac and 355.0 dc
End Application:
Switch limit
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit
Switch Actuating Force:
92.0 inch-ounces
Actuator Movement:
0.275 pretravel inches and 0.020 overtravel inches and 0.020 differential inches

100.000 milliamperes resistive dc and 6.000 amperes resistive ac

**Contact Load Current Rating At Maximum Rated Voltage:** 

## **NSN 5930-01-113-5714** Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:	
4 screw	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A053a0