NSN 5930-01-113-9121

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-113-9121

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
1.050 inches
Overall Width:
1.375 inches
Body Length:
1.940 inches
Body Width:
1.375 inches
Body Height:
0.830 inches
Unthreaded Mounting Hole Diameter:
0.139 inches
Actuator Length:
2.312 inches
Actuator Style:
Leaf
Actuator Width:
0.190 inches
Actuator Free Position Height:
Between 0.710 inches and 0.745 inches
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
End Application:
F/tf-15a aircraft e/i 76301
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
0.5 ounces
Switch Actuating Force:
8.0 ounces
Actuator Movement:
Between 0.020 overtravel inches and 0.109 differential inches

NSN 5930-01-113-9121

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage	Contact Load	Current Rating	At Maximum	Rated	Voltage
--	--------------	-----------------------	------------	-------	---------

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0