NSN 5930-01-114-2368

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-114-2368

view Offilite at https://aerobasegroup.com/hsh/5550-01-114-2500
Hazardous Locations/environmental Protection:
General purpose-nema type 1
Overall Length:
0.956 inches
Overall Height:
0.300 inches
Body Diameter:
0.660 inches
End Application:
An/uyh-2 dp 52088
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -10.0 degrees fahrenheit and 250.0 degrees fahrenheit
Mounting Method:
Clamp
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 1.0 amperes lamp load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
170.00 actuation point degrees fahrenheit and 166.00 deactuation point degrees fahrenheit and 168.00 deactuation point degrees
fahrenheit and 2.00 differential point degrees fahrenheit and 4.00 differential point degrees fahrenheit
Contact Voltage Rating In Volts:
28.0 dc at sea level second voltage
Frequency In Hertz:
60.0 first voltage
Media For Which Designed:
Gas or liquid
Unpackaged Unit Weight:
12.000 grams
Style Designator:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

Test Data Document:

Disc

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

NSN 5930-01-114-2368

Thermostatic Switch - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-s-24236/20 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0