# NSN 5930-01-114-3459

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-114-3459

#### **Thread Class:**

2b single mounting facility

#### **Overall Length:**

2.376 inches

# **Overall Height:**

2.250 inches

### **Overall Width:**

2.250 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.938 inches single actuator

#### Individual Section Quantity:

1

#### Longest Horizontal Distance Between Mounting Centers:

1.500 inches single mounting facility

## **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

End Application:

Se test fixt

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

2 single section rear

#### Throw Quantity:

12 single section rear

#### **Mounting Method:**

Threaded hole single mounting facility

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### **Thread Size:**

0.164 inches single mounting facility

### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

#### **Mounting Facility Pattern:**

Two position in-line single mounting facility

# Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round single actuator

#### **Terminal Type:**

Turret

# NSN 5930-01-114-3459

Rotary Switch - Page 2 of 2



Contact Switching Action: Breaks before makes single section rear Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator Contact Load Current Rating: 250.0 milliamperes resistive load dc at sea level Style Designator: Tap, square frame Thread Series Designator: Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0