

View Online at <https://aerobasegroup.com/nsn/5930-01-114-5071>

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

2.591 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

1.170 inches

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3: 00 o'clock

End Application:

Frm 86 77777

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

8 each section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Pull to turn

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level and 2.0 amperes inductive load ac at sea level

Special Features:

Shaft flat has vee cut of 45 degrees angle and 0.055 in. Deep

Precious Material And Location:

Contacts and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0