NSN 5930-01-114-5262

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-114-5262

Dustproof
Overall Length:
12.938 inches
Overall Height:
10.000 inches
Overall Width:
3.969 inches
Unthreaded Mounting Hole Diameter:
0.312 inches single mounting facility
Individual Section Quantity:
1
Knob Manufacturer Code:
82121
Longest Horizontal Distance Between Mounting Centers:
3.062 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
9.406 inches single mounting facility
Operating Tempurature Range:
-20.0/+150.0 degrees fahrenheit
End Application:
Switchboard g 34008
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section rear
Throw Quantity:
7 single section rear
Mounting Method:
Unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
28.0 lowest dc voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
7 single actuator
Terminal Type:
Screw
Contact Switching Action:

Breaks before makes single section rear

NSN 5930-01-114-5262

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

45.0 degrees single actuator

Detent Rotational Torque Range:

+0.500/+50.000 inch-pounds single actuator

Contact Load Current Rating:

5.0 amperes resistive load lowest dc voltage rating at sea level

Style Designator:

Tap, square frame

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0