NSN 5930-01-114-5265

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-114-5265

Body Style:				
Hole mounted				
Hazardous Locations/environmental Protection:				
Corrosion resistant and watertight				
Overall Height:				
8.437 inches				
Overall Width:				
4.312 inches				
Case Material:				
Metal				
Actuator Length:				
11.500 inches				
Actuator Style:				
Adjustable arm				
Housing Height:				
5.312 inches				
Housing Length:				
3.812 inches				
Housing Width:				
4.312 inches				
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:				
7.812 inches				
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:				
2.375 inches				
Maximum Voltage Rating In Volts:				
440.0 ac and 230.0 dc				
End Application:				
Casrep item 03950				
Inclosure Type:				
Fully enclosed				
Nonpile-up Contact Arrangement:				
2 pole, single throw, normally closed, momentary action single switch unit				
Switch Actuating Force:				
88.0 ounces				
Contact Load Current Rating At Maximum Rated Voltage:				
5.000 amperes resistive dc and 20.000 amperes resistive ac				
Precious Material And Location:				
Contacts silver				
Terminal Type And Quantity:				
4 screw				
Shelf Life:				
N/a				

NSN 5930-01-114-5265

Sensitive Switch - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0