

View Online at <https://aerobasegroup.com/nsn/5930-01-114-5268>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

1.154 inches

Overall Height:

2.720 inches

Overall Width:

0.904 inches

Body Height:

2.440 inches

Case Material:

Metal

Actuator Length:

1.120 inches

Actuator Style:

Rectangular

Actuator Height:

0.070 inches

Actuator Width:

0.870 inches

Actuator Color:

White single actuator and white single actuator and white single actuator and white single actuator

Illuminated Actuator Color:

Yellow single actuator and yellow single actuator and green single actuator and green single actuator

Actuator Inscription:

Dicke fix; on) (dicke fix; off) single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

An/sps 49 49956

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

Special Features:

Spacer; mtg sleeve

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0