NSN 5930-01-114-5268

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-114-5268

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Moisture proof
Overall Length:
1.154 inches
Overall Height:
2.720 inches
Overall Width:
0.904 inches
Body Height:
2.440 inches
Case Material:
Metal
Actuator Length:
1.120 inches
Actuator Style:
Rectangular
Actuator Height:
0.070 inches
Actuator Width:
0.870 inches
Actuator Color:
White single actuator and white single actuator and white single actuator and white single actuator
Illuminated Actuator Color:
Yellow single actuator and yellow single actuator and green single actuator and green single actuator
Actuator Inscription:
Dicke fix; on) (dicke fix; off) single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
An/sps 49 49956
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000

Special Features:

Spacer; mtg sleeve

amperes inductive ac and 750.000 milliamperes lamp ac

NSN 5930-01-114-5268

Push Switch - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0