NSN 5930-01-114-8294

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-114-8294

| Body Style: |
|--|
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Moisture proof |
| Overall Length: |
| 1.154 inches |
| Overall Height: |
| 2.720 inches |
| Overall Width: |
| 0.904 inches |
| Body Height: |
| 2.440 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 1.120 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.070 inches |
| Actuator Width: |
| 0.870 inches |
| Actuator Color: |
| White single actuator and white single actuator and white single actuator and white single actuator |
| Illuminated Actuator Color: |
| Green single actuator and green single actuator and yellow single actuator and yellow single actuator |
| Actuator Inscription: |
| Jdf; on) (jdf; off) single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| End Application: |
| An/sps 49 49956 |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 2 000 amperes resistive do and 1 000 amperes inductive do and 750 000 milliamperes lamp do and 2 000 amperes resistive ac and 1 00 |

Special Features:Spacer; mtg sleeve

amperes inductive ac and 750.000 milliamperes lamp ac

NSN 5930-01-114-8294

Push Switch - Page 2 of 2



| Terminal Type A | and Quantity | /: |
|-----------------|--------------|-----------|
|-----------------|--------------|-----------|

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0