

View Online at <https://aerobasegroup.com/nsn/5930-01-114-9866>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Body Diameter:**

1.500 inches

**Bushing Length:**

1.000 inches

**Body Length:**

1.700 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Free Position Height:**

3.500 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

80.0 ounces

**Switch Actuating Force:**

Between 96.0 ounces and 192.0 ounces

**Actuator Movement:**

Between 0.070 pretravel inches and 0.250 overtravel inches and 0.045 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes motor dc

**Special Features:**

Wire leads awg 18, 72.000 in. Min lg, striped 0.375 in.

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

8 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0