NSN 5930-01-115-1832

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-115-1832

| Body Style: |
|---|
| Panel mounted |
| Hazardous Locations/environmental Protection: |
| Explosion proof and humidity resistant |
| Overall Length: |
| 3.340 inches |
| Overall Height: |
| 1.125 inches |
| Overall Width: |
| 1.000 inches |
| Body Width: |
| 0.937 inches |
| Body Height: |
| 0.937 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.740 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.240 inches |
| Actuator Width: |
| 0.740 inches |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Mounting Surface To Terminal End Distance: |
| 3.160 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Full display lens |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 1.000 amperes resistive dc and 1.000 amperes resistive ac |
| Terminal Type And Quantity: |
| 1 socket, integrated wire termination |
| Shelf Life: |
| M/- |

N/a

NSN 5930-01-115-1832

Push Switch - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV | еа | SU | ıre: |

--

Demilitarization:

No

Fiig:

A053a0