Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-115-2615

Hazardous Locations/environmental Protection:

Explosion proof and watertight

Overall Length:

4.938 inches

Overall Height:

4.625 inches

Overall Width:

2.875 inches

Body Length:

4.875 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

End Application:

Ffg-7 class 12345

Pressure Switch Type:

Gage

Operating Tempurature Rating:

Between -30.0 degrees fahrenheit and 580.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

216.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Screw

NSN 5930-01-115-2615

Pressure Switch - Page 2 of 2



Contact Load Current Rating:

9.6 amperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+10.00/+180.00 actuation point pounds per square inch and +10.00/+165.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0