

View Online at <https://aerobasegroup.com/nsn/5930-01-115-4243>

**Hazardous Locations/environmental Protection:**

Weatherproof

**Overall Height:**

5.750 inches

**Overall Width:**

2.370 inches

**Body Height:**

3.000 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.720 inches

**Longest Vertical Distance Between Mounting Centers:**

2.720 inches

**End Application:**

Basic device

**Pressure Switch Type:**

Gage

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Electrical access port and tamper proof cap

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Decrease

**Proof Pressure:**

7000.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

30.0 milliamperes resistive load third voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+100.00/+1400.00 actuation point pounds per square inch and +130.00/+1500.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Voltage Rating In Volts:**

6.0 dc at sea level fourth voltage

**Pressure Connector Type:**

Inverted flare, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0