

View Online at <https://aerobasegroup.com/nsn/5930-01-115-4244>

**Overall Length:**

2.000 inches

**Overall Diameter:**

1.690 inches

**End Application:**

3930-01-076-4237. Tarawa class lha, austin ship class lpd-4 amphibious transport docks, wasp class lhd, shipboard material handling equipment (mhe), whidbey island class lsd, truck, fl (m4k)

**Pressure Switch Type:**

Gage

**Mounting Method:**

Inlet connection

**Features Provided:**

Hermetically sealed case

**Thready Qty Per Inch (tpi):**

27 single pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.125 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

4.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

20.00 actuation point pounds per square inch and 17.00 deactuation point pounds per square inch and 3.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

6.0 dc at sea level second voltage

**Pressure Connector Type:**

Inverted flare, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Thread Series Designator:**

Nptf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0