

View Online at <https://aerobasegroup.com/nsn/5930-01-115-4244>

Overall Length:

2.000 inches

Overall Diameter:

1.690 inches

End Application:

3930-01-076-4237. Tarawa class lha, austin ship class lpd-4 amphibious transport docks, wasp class lhd, shipboard material handling equipment (mhe), whidbey island class lsd, truck, fl (m4k)

Pressure Switch Type:

Gage

Mounting Method:

Inlet connection

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

4.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

20.00 actuation point pounds per square inch and 17.00 deactuation point pounds per square inch and 3.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

6.0 dc at sea level second voltage

Pressure Connector Type:

Inverted flare, threaded external single connection

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0