

View Online at <https://aerobasegroup.com/nsn/5930-01-115-4252>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.549 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Overall Height:

0.887 inches

Overall Width:

0.400 inches

Body Length:

1.094 inches

Body Width:

0.400 inches

Body Height:

0.735 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.110 inches

Actuator Style:

Rectangular

Actuator Height:

0.062 inches

Actuator Width:

0.165 inches

Actuator Free Position Height:

0.578 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

End Application:

Trk frklft 30612

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

15.0 grams

Switch Actuating Force:

135.0 grams

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 15.000 amperes resistive ac

Special Features:

U/I and tv-3 rating

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0