

View Online at <https://aerobasegroup.com/nsn/5930-01-115-5121>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.250 inches

Outside Diameter:

0.112 inches all connections

Overall Height:

1.130 inches

Overall Width:

2.250 inches

Mounting Slot Width:

0.160 inches

Body Length:

2.000 inches

Longest Horizontal Distance Between Mounting Centers:

1.750 inches

Longest Vertical Distance Between Mounting Centers:

0.880 inches

End Application:

Target g n el 76301

Pressure Switch Type:

Gage

Mounting Method:

Slot and threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.138 inches all threaded hole

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+1.00/+16.00 actuation point inches of water and +1.00/+16.00 deactuation point inches of water

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

15.00 differential point inches of water

Contact Voltage Rating In Volts:

300.0 ac at sea level single voltage

Pressure Connector Type:

Plain, unthreaded external all connections

Media For Which Designed:

Gas

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0