NSN 5930-01-115-5123

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-115-5123

| Thread Class: |
|---|
| 2a |
| Body Style: |
| Bushing mounted |
| Hazardous Locations/environmental Protection: |
| Watertight |
| Overall Length: |
| 0.520 inches |
| Overall Height: |
| 1.704 inches |
| Overall Width: |
| 0.472 inches |
| Bushing Length: |
| 0.315 inches |
| Body Length: |
| 0.520 inches |
| Body Width: |
| 0.472 inches |
| Case Material: |
| Metal or plastic |
| Actuator Diameter: |
| 0.315 inches |
| Actuator Height: |
| 0.405 inches |
| Actuator Color: |
| Red single actuator |
| Maximum Voltage Rating In Volts: |
| 125.0 ac and 28.0 dc |
| End Application: |
| 6610-01-074-4652 |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 40 |
| Thread Size: |
| 0.250 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

NSN 5930-01-115-5123Push Switch - Page 2 of 2



| Inread Series Designator: |
|-----------------------------|
| Uns |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0