

View Online at <https://aerobasegroup.com/nsn/5930-01-115-7327>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.633 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.560 inches single actuator

Overall Diameter:

0.750 inches

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees celsius

End Application:

5820-01-108-9658

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Shaft Flat/slot Angular Location:

195.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+4.000/+32.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

300.0 milliamperes resistive load dc at sea level and 150.0 milliamperes inductive load dc at sea level

Precious Material And Location:

Contacts and terminal surfaces gold and contacts silver

Precious Material:

Gold and silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0