

View Online at <https://aerobasegroup.com/nsn/5930-01-116-4466>

Thread Class:

2a single mounting facility

Thread Length:

0.412 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.700 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.220 inches single actuator

Overall Diameter:

2.000 inches

Individual Section Quantity:

3

End Application:

Fcs mk 116 mo 08783

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

7 each section front

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

7 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Screw

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Precious Material And Location:

Rotor and stationary contacts surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0