

View Online at <https://aerobasegroup.com/nsn/5930-01-116-4874>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Fungus resistant

Body Diameter:

1.000 inches

Bushing Length:

1.000 inches

Body Length:

Between 1.045 inches and 1.075 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.245 inches and 0.255 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

1.375 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

M110 howitzer family

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded stud

Thread Size:

0.625 inches

Switch Release Force:

64.0 ounces

Switch Actuating Force:

Between 64.0 ounces and 192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac and 5.000 amperes inductive ac and 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 4.000 amperes motor dc

Special Features:

Cables 10.000 lg from switch c/l

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 cable w/connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0