NSN 5930-01-116-5140Push Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-116-5140 |
|--|
| Thread Class: |
| 2a |
| Body Style: |
| Bushing mounted |
| Overall Length: |
| 1.880 inches |
| Overall Height: |
| 0.620 inches |
| Overall Width: |
| 0.620 inches |
| Body Diameter: |
| 0.620 inches |
| Bushing Length: |
| 0.440 inches |
| Body Length: |
| 1.000 inches |
| Actuator Diameter: |
| 0.380 inches |
| Actuator Height: |
| 0.280 inches |
| Actuator Color: |
| White single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.469 inches |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes |
| inductive ac and 1.000 amperes lamp ac |
| Precious Material And Location: |
| Contacts silver and contact surfaces gold |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Thread Series Designator: |

Uns

NSN 5930-01-116-5140

Push Switch - Page 2 of 2



| Terminal Type | And | Quantity: |
|---------------|-----|-----------|
|---------------|-----|-----------|

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0