

View Online at <https://aerobasegroup.com/nsn/5930-01-116-5532>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.572 inches

Overall Height:

1.862 inches

Overall Width:

0.556 inches

Bushing Length:

0.469 inches

Body Length:

0.572 inches

Body Width:

0.556 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.687 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

6940-01-046-2850

Mounting Surface To Terminal End Distance:

0.706 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 2.000 amperes inductive ac

Precious Material And Location:

Terminal surfaces gold

Test Data Document:

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

96906-ms90311 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0