NSN 5930-01-116-5535

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-116-5535

Darles Officials
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Waterproof
Overall Length:
4.875 inches
Overall Height:
1.781 inches
Overall Width:
1.656 inches
Case Material:
Metal
Actuator Style:
Roller plunger
Actuator Free Position Height:
2.281 inches
Actuator Roller Diameter:
0.438 inches
Actuator Roller Width:
0.156 inches
Housing Height:
1.781 inches
Housing Length:
2.844 inches
Housing Width:
1.656 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.344 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
440.0 ac and 230.0 dc
End Application:
Casrep item 03950
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, two positions momentary single switch unit
Actuator Movement:

Contact Load Current Rating At Maximum Rated Voltage:

200.000 milliamperes resistive dc and 6.000 amperes resistive ac

0.040 pretravel inches and 0.280 overtravel inches and 0.020 differential inches

NSN 5930-01-116-5535

Sensitive Switch - Page 2 of 2



l erminal	Type And	Quantity:
3 screw		

Shelf Life: N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0