

View Online at <https://aerobasegroup.com/nsn/5930-01-116-5535>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

4.875 inches

Overall Height:

1.781 inches

Overall Width:

1.656 inches

Case Material:

Metal

Actuator Style:

Roller plunger

Actuator Free Position Height:

2.281 inches

Actuator Roller Diameter:

0.438 inches

Actuator Roller Width:

0.156 inches

Housing Height:

1.781 inches

Housing Length:

2.844 inches

Housing Width:

1.656 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.344 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

Maximum Voltage Rating In Volts:

440.0 ac and 230.0 dc

End Application:

Casrep item 03950

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Actuator Movement:

0.040 pretravel inches and 0.280 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

200.000 milliamperes resistive dc and 6.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0