

View Online at <https://aerobasegroup.com/nsn/5930-01-116-5539>

Thread Class:

2a

Body Style:

Bushing mounted

Overall Length:

2.175 inches

Overall Height:

0.640 inches

Overall Width:

0.640 inches

Body Diameter:

0.562 inches

Bushing Length:

0.425 inches

Body Length:

1.010 inches

Case Material:

Metal

Actuator Length:

0.500 inches

Actuator Style:

Rectangular

Actuator Height:

0.505 inches

Actuator Width:

0.500 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Trng dev ce 94987

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

5 tab, solder lug

Specification Data:

81349-mil-s-22885/79 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0