NSN 5930-01-116-8273

Rotary Switch - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5930-01-116-8273

2b single mounting facility						
Overall Length:						
5.062 inches						
Overall Height:						
2.250 inches						
Overall Width:						
2.250 inches						
Shaft Diameter:						
0.250 inches single actuator						
Shaft Length:						
0.938 inches single actuator						
Individual Section Quantity:						
4						
Longest Horizontal Distance Between Mounting Centers:						
1.500 inches single mounting facility						
Operating Tempurature Range:						
-55.0/+125.0 degrees celsius						
End Application:						
4920-01-054-5641 81755						
Switch Contact Basic Design:						
Nonpile-up symmetrical						
Pole Quantity:						
4 each section front						
Throw Quantity:						
7 each section front						
Mounting Method:						
Threaded hole single mounting facility						
Thready Qty Per Inch (tpi):						
32 single mounting facility						
Thread Size:						
0.164 inches single mounting facility						
Contact Voltage Rating In Volts:						
28.0 dc at sea level						
Mounting Facility Pattern:						
Two position in-line single mounting facility						
Switch Actuator Indexing Position Quantity:						
7 single actuator						
Shaft Type:						
Round single actuator						
Terminal Type:						
Pin						

NSN 5930-01-116-8273

Rotary Switch - Page 2 of 2



Con	tact	Swit	chino	ı Acti	on:
	ıavı	OWIL	CHILL	ı Actı	vii.

Breaks before makes each section front

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 3.0 amperes inductive load dc at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0