NSN 5930-01-116-8422

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-116-8422

View Online at https://aerobasegroup.com/nsn/5930-01-116-8422
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.700 inches
Overall Height:
0.375 inches
Unthreaded Mounting Hole Diameter:
Between 0.140 inches and 0.170 inches
Distance Between Mounting Facility Centers:
Between 1.370 inches and 1.390 inches
End Application:
4920-01-054-5641
Tempurature Sensing Element Type:
nternal sensor
Operating Tempurature Rating:
350.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
I pole, single throw, normally closed, momentary action
Ferminal Type:
Tab, solder lug
Contact Load Current Rating:
3.3 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
150.00 actuation point degrees fahrenheit and 160.00 actuation point degrees fahrenheit and 32.00 differential point degrees fahrenhe
and 38.00 differential point degrees fahrenheit
Contact Voltage Rating In Volts:
120.0 ac at sea level single voltage
Media For Which Designed:
Gas
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5930-01-116-8422

Thermostatic Switch - Page 2 of 2

Fiig: A048b0

