NSN 5930-01-117-2764

Pressure Switch - Page 1 of 2

Cylindrical



View Online at https://aerobasegroup.com/nsn/5930-01-117-2764

Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
3.500 inches
Overall Diameter:
1.120 inches
End Application:
Bleed air sys
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 300.0 degrees fahrenheit
Mounting Method:
Input port
Features Provided:
Electrical box connector
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
190.00 pounds per square inch gage
Thread Size:
0.438 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
2.000 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
150.00 actuation point pounds per square inch gage and 120.00 deactuation point pounds per square inch gage and 30.00 differential point
pounds per square inch gage
Contact Voltage Rating In Volts:
28.0 dc at sea level single voltage
Pressure Connector Type:
Flared, threaded external single connection
Media For Which Designed:
Gas
Style Designator:

NSN 5930-01-117-2764

Pressure Switch - Page 2 of 2



Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0