## NSN 5930-01-117-3550

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-117-3550

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
6.965 inches
Overall Height:
2.730 inches
Overall Width:
1.650 inches
Actuator Length:
3.750 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.320 inches
Housing Height:
1.780 inches
Housing Length:
2.840 inches
Housing Width:
1.650 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.342 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.156 inches
Maximum Voltage Rating In Volts:
440.0 ac and 355.0 dc
End Application:
Conveyor vert
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Thread Size:
0.190 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Actuating Force:

32.0 ounces

## NSN 5930-01-117-3550

Sensitive Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

100.000 milliamperes resistive dc and 6.000 amperes resistive ac

**Special Features:** 

Two mtg holes thd

**Thread Series Designator:** 

Unf

**Terminal Type And Quantity:** 

3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0