

View Online at <https://aerobasegroup.com/nsn/5930-01-117-9780>

Body Style:

Bushing mounted

Body Diameter:

0.385 inches

Bushing Length:

Between 0.869 inches and 0.931 inches

Body Length:

0.880 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

Between 0.213 inches and 0.223 inches

Actuator Height:

Between 0.145 inches and 0.175 inches

Actuator Free Position Height:

Between 0.145 inches and 0.175 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Used on ifv m2a1

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded stud

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Switch Release Force:

24.0 ounces

Switch Actuating Force:

112.0 ounces

Actuator Movement:

0.020 pretravel inches and 0.125 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0