

View Online at <https://aerobasegroup.com/nsn/5930-01-117-9780>

**Body Style:**

Bushing mounted

**Body Diameter:**

0.385 inches

**Bushing Length:**

Between 0.869 inches and 0.931 inches

**Body Length:**

0.880 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.213 inches and 0.223 inches

**Actuator Height:**

Between 0.145 inches and 0.175 inches

**Actuator Free Position Height:**

Between 0.145 inches and 0.175 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

Used on ifv m2a1

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded stud

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

24.0 ounces

**Switch Actuating Force:**

112.0 ounces

**Actuator Movement:**

0.020 pretravel inches and 0.125 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0