

View Online at <https://aerobasegroup.com/nsn/5930-01-118-0402>

Thread Length:

9.52 millimeters single mounting facility

Overall Length:

150.05 millimeters

Shaft Diameter:

6.30 millimeters single actuator and 6.37 millimeters single actuator

Shaft Length:

47.63 millimeters single actuator

Overall Diameter:

33.32 millimeters

Nonturn Device Radius:

11.10 millimeters at 9: 00 o'clock

Individual Section Quantity:

6

Nonturn Device Type:

Tab at 5: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

11 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

11 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

1.5 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0