NSN 5930-01-118-2533

Thermostatic Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-118-2533

| Hazardous Locations/environmental Protection: |
|---|
| Moisture proof |
| End Application: |
| 10k forklift 30612 |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 14 single threaded bushing |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.500 inches single threaded bushing |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Terminal Type: |
| Tab, solder lug |
| Contact Adjustability: |
| Deactuation point not adjustable and actuation point not adjustable |
| Contact Stimulus Rating: |
| 120.00 actuation point degrees fahrenheit and 250.00 actuation point degrees fahrenheit |
| Media For Which Designed: |
| Liquid |
| Thread Series Designator: |
| Npt single threaded bushing |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A048b0 |
| |
| |