# NSN 5930-01-118-2538

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-118-2538

Padu Stular
Body Style: Panel mounted
Hazardous Locations/environmental Protection:
Waterproof
Overall Length:
2.960 inches
Overall Height:
0.740 inches
Overall Width:
0.740 inches
Body Width:
0.740 inches
Body Height:
0.740 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
0.300 inches
Actuator Width:
0.740 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Oliver perry class ffg; assault amphibious vehicle, command (aavc-7a1); ffg-7 fin stabilizer system (fss)
Mounting Surface To Terminal End Distance:
2.660 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

## NSN 5930-01-118-2538

Push Switch - Page 2 of 2



Feat

### **Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

#### **Special Features:**

Weapon system essential

#### **Precious Material And Location:**

Terminals gold

#### **Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

11 pin

#### **Specification Data:**

81349-mil-s-22885/80 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0