

View Online at <https://aerobasegroup.com/nsn/5930-01-118-3435>

Thread Class:

2a single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.750 inches

Individual Section Quantity:

3

End Application:

Cabinet power 07482

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

3 each section periphery

Mounting Facility Circle Radius:

2.812 inches single mounting facility

Mounting Method:

Threaded stud single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

16 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

120.0 ac at sea level

Mounting Facility Pattern:

Three position circular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks, breaks before makes each section periphery

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0