

View Online at <https://aerobasegroup.com/nsn/5930-01-118-4392>

**Body Style:**

Bushing mount

**Overall Length:**

0.572 inches

**Overall Height:**

1.410 inches

**Overall Width:**

0.556 inches

**Bushing Length:**

0.170 inches

**Body Length:**

0.572 inches

**Body Width:**

0.556 inches

**Body Height:**

0.600 inches

**Actuator Style:**

Round

**Actuator Height:**

0.440 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

An/arc-190 13499

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes resistive ac

**Precious Material And Location:**

Terminals surfaces gold

**Test Data Document:**

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 printed circuit

**Specification Data:**

96906-ms21355 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0