

View Online at <https://aerobasegroup.com/nsn/5930-01-118-4392>

Body Style:

Bushing mount

Overall Length:

0.572 inches

Overall Height:

1.410 inches

Overall Width:

0.556 inches

Bushing Length:

0.170 inches

Body Length:

0.572 inches

Body Width:

0.556 inches

Body Height:

0.600 inches

Actuator Style:

Round

Actuator Height:

0.440 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

An/arc-190 13499

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Terminals surfaces gold

Test Data Document:

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 printed circuit

Specification Data:

96906-ms21355 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0