

View Online at <https://aerobasegroup.com/nsn/5930-01-118-5767>

Thread Class:

3a single threaded bushing

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

52.3 millimeters

Body Diameter:

0.312 inches

Body Length:

15.9 millimeters

End Application:

Mk75modo gun 44114

Tempurature Sensing Element Type:

Bulb

Width Across Flats:

19.1 millimeters

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

20 single threaded bushing

Contact Action Stimulus:

Decrease

Thread Size:

0.500 inches single threaded bushing

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load second voltage and 500.0 milliamperes inductive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

30.00 actuation point degrees celsius and 27.00 deactuation point degrees celsius and 3.00 differential point degrees celsius

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Thread Series Designator:

Unf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0